

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
14 July 2005 (14.07.2005)

PCT

(10) International Publication Number
WO 2005/064701 A2

(51) International Patent Classification⁷: **H01L 41/09**

PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoud-
seweg 1, NL-5621 BA Eindhoven (NL).

(21) International Application Number:
PCT/IB2004/052868

(71) Applicant (*for DE only*): **PHILIPS INTELLECTUAL
PROPERTY & STANDARDS GMBH** [DE/DE]; Stein-
damm 94, 20099 Hamburg (DE).

(22) International Filing Date:
20 December 2004 (20.12.2004)

(72) Inventors; and

(25) Filing Language: English

(75) Inventors/Applicants (*for US only*): **KLEE, Marcike, K.**
[DE/DE]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven
(NL). **RIJKS, Theodoor, G., S., M.** [NL/NL]; c/o Prof.
Holstlaan 6, NL-5656 AA Eindhoven (NL). **LOK, Pieter**
[NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven
(NL). **MAUCZOK, Ruediger, G.** [DE/DE]; c/o Prof. Hol-
stlaan 6, NL-5656 AA Eindhoven (NL).

(26) Publication Language: English

(30) Priority Data:
03104892.9 22 December 2003 (22.12.2003) EP


(71) Applicant (*for AE, AG, AL, AM, AT, AU, AZ, BA, BB, BE,
BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CY, CZ,
DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM,
HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK,
LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ,
NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD,
SE, SG, SK, SL, SY, SZ, TJ, TM, TN, TR, TT, TZ, UA, UG,
UZ, VC, VN, YU, ZA, ZM, ZW only*): **KONINKLIJKE**

(74) Agents: **ELEVELD, Koop, J. et al.**; Prof. Holstlaan 6,
NL-5656 AA Eindhoven (NL).

(81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,

[Continued on next page]

(54) Title: ELECTRONIC DEVICE



(57) Abstract: The microelectromechanical system (MEMS) element (101) comprises a first electrode (31) that is present on a surface of a substrate (30) and a movable element (40). This overlies at least partially the first electrode (31) and comprises a piezo-electric actuator, which movable element (40) is movable towards and from the substrate (30) by application of an actuation voltage between a first and a second position, in which first position it is separated from the substrate (30) by a gap. Herein the piezoelectric actuator comprises a piezoelectric layer (25) that is on opposite surfaces provided with a second and a third electrode (21,22) respectively, said second electrode (21) facing the substrate (30) and said third electrode (22) forming an input electrode of the MEMS element (101), so that a current path between through the MEMS element (101) comprises the piezoelectric layer (25) and the tunable gap.



KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report

- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.